



HYDRAULIC TILT TRAILER

The Adams heavy-duty, tandem axle, hydraulic tilt trailer makes it easy to transport empty poly tanks from one location to another. The tilt trailer comes standard with a 5.5 HP Honda gas engine with a hydraulic pump to operate the hydraulic lift. The Adams tilt trailer also features a tool box to store the straps and a winch bar mounted on the frame of the trailer for easy access.

1040 W. Charter Way Stockton, California 95206 800-922-7253 3766 S. Bagley Avenue Fresno, California 93725 800-532-0253 21930 Rosehart Way Salinas, CA 93908 844-755-2410

4285 Gila Ridge Road Yuma, Arizona 85365 800-752-2636

HYDRAULIC TILT TRAILER

STANDARD FEATURES & SPECIFICATIONS:

- Tube constructed frame
- Henschen suspension axles
- Two safety chains
- Fenders
- Stop and turn signal lights
- 12.5L x 15 highway/implement tires
- Honda 5.5 HP gas engine/hydraulic drive
- Three 4" wide straps to secure tank to trailer
- Heavy duty pump base mounted on the front
- Capacity: 120" diameter tanks x 180" in length
- Tongue jack
- Tool box
- · Winch: weld-on, mounted on outriggers
- Winch bar

Sii

TY IST

100

- Dimensions: width 92" x length 264" (22ft.) x height 40"
- Powder coated frame black in color



Manufactured by Industrial Iron Works/Adams Fertilizer Equipment

197

2022